

# SD DEGREASER

Surface cleaner/degreaser and wax remover



## PRODUCT DESCRIPTION

Nautix SD degreaser is concentrated solvent developed for hull preparation and for cleaning surface to be painted with no damage to gelcoat or paintwork.

It's particularly adapted to clean new GRP hull and SD remove wax providing from moulding, but also oil and other contamination.

Nautix SD degreaser is very liquid, less volatile and inflammable than acetone, but provides higher efficiency.

It can be applied over tools which have been used for resin application.

## PRODUCT INFORMATION

Finish	Translucent
Flash point	23 < FP < 61°C
Packaging	0.75L – 2.5L – 5L
Shelf life	5 years

Suitable for use on :

- GRP
- Steel
- Aluminium
- Wood

## SAFETY INFORMATION

- Work in well-ventilated area (ensure adequate ventilation during use), wear suitable protective clothing, gloves, glasses and eye/face protection. Unprotected person must be kept away from treatment area. Dispose of protective gloves and equipment after use.
- Read the label safety section for Health and Safety Information before application.

## APPLICATION

- Clean the surface with a washing product (detergent + fresh water), rinse and let dry.
- Apply Nautix SD degreaser to a damp cloth or sponge, then wipe the whole surface to be cleaned using moderate pressure.
- Clean the surface with dried cloth or sponge.
- Change the cloth regularly during cleaning.
- Wait for complete evaporation before painting

## TRANSPORT, STORAGE, AND SAFETY INFORMATION

### Transport and storage

- This product should be kept in securely closed containers during transport and storage.
- Exposure to air, sun, and extreme temperatures should be avoided. For the full shelf-life of the paint, be sure that the container is firmly closed between use and the storage temperature is between 10° and 25°C. Keep out of direct sunlight.

### Safety

- Before use, read the label safety section for Health and Safety Information. For further details, please contact Nautix or its distributors.
- All professional operators must wear suitable protective clothing : coveralls of a contrasting colour to the product being applied, underneath a disposable coverall with hood, suitable gloves and impervious footwear that protects the lower leg. Wear suitable respiratory equipment (such as air fed respiratory protective equipment with combined protective helmet and visor) when spraying.

### Disposal

- Disposal of remainders must be arranged for in consultation with the authorities. Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of this product cannot be disposed of through the municipal waste route or dumped without permit.

### General

- The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk. Nautix can accept no responsibility for the performance of the product or for any loss or damage. The information contained in this sheet is liable to modification from time to time.

