

# Nautix - Antifoulings compatibility

## Which antifouling is compatible with Nautix products?

Once you've identified the Nautix antifouling that's most suitable, if you have an existing coating on your hull you will need to establish the compatibility of the two products. Use this simple table to check compatibility between Nautix antifoulings and also with competitor products.

EXISTING ANTIFOULING (in good condition)		Products	NEW ANTIFOULING										
			A1	A2	A3	A3 FORMULA+	A3T. SPEED	A4	A4T. SPEED	A88	MARIN	PERFORMER	
NAUTIX	A1												
	A2												
	A3												
	A3 FORMULA+												
	A3T.SPEED												
	A4												
	A4T.SPEED												
	A88												
	MARIN												
	PERFORMER												
INTERNATIONAL	Micron Optima - Micron Extra EU - Micron Extra 2 - Micron WA - Micron 66/77												
	Cruiser Uno - Cruiser Uno EU - Boatgard EU - Uni Pro												
	Trilux - Trilux 33 - VC Offshore - VC Offshore EU												
	Interspeed Ultra 2 - Cruiser Bright White - Ultra EU												
	VC17M Extra												
BOERO	Altura 619 - Corsa Regatta 619 - Scirocco 622												
	Mistral - Mistral 633 - Season 952 - Corsa 642												
	Hydrocoat												
HEMPEL / BLAKES	AluXtra - Globic - Tiger Ultra/Cruising - Cruising Performer - Mille (Dynamic / Ultimate) - Olympic												
	Bravo - Hard racing - Hard Racing Ultra												
	Glide speed - Water glide												
JOTUN	Mare Nostrum - Non Stop - Performance - Super Sargasso												
	Racing / Racing Ultraspeed												
	Jotun Super Tropic												
SEAJET PLASTIMO	Classic												
	Performance - Racing												
SEAJET	031 Samurai - 033 Shogun - 034 Emporor - 038 Alusave - 039 Platinum												
	030 Warrior - 037 Coastal												
EXISTING ANTIFOULING (in bad condition)	Antifouling with PTFE												
	Hard matrix Antifouling												
	Self-polishing Antifouling												
	Unknown Antifouling												
	Tin-based Antifouling												
	Antifouling in bad condition												

I N F O R M A T I O N S	APPLY DIRECTLY	Apply directly once the surface is dry and clean
	WET SAND + NEW COAT	Wet sand with a medium grade sand paper and rinse well with fresh water. Apply new coat once the surface is dry and clean
	WET SAND + P1 PRIMER	Wet sand with a medium grade sand paper and rinse well with fresh water. Apply one sealer coat of Nautix P1
	COMPLETE REMOVAL	Do not apply any paint. Complete removal of existing paint is necessary with Nautix Stripper.

**Nautix STRIPPER** : Stripper especially developed to remove old/unknown antifoulings without damaging the surface (included GRP)

